SPECIFICATION SHEET



Trebro - TSR

Trebro Manufacturing, Inc. is pleased to announce the introduction of the all new TSR automatic stacking roll turf harvester. This exciting new machine incorporates proven Trebro technology coupled with many new and innovative features. Powered by a 140 horsepower John Deere engine with all-wheel hydrostatic drive, this rugged machine is capable of performing in a wide variety of harvesting conditions.

...proven Trebro technology coupled with many new and innovative features.

A quiet, comfortable operator's cab rotates 90° to place the operator in the best position to see all of the harvesting and stacking functions. A variety of cutting widths are available, including 16 inch, 21 inch, 23 inch and 24 inch. The proven Trebro floating cutting head with dual adjustable down pressure produces a remarkable quality of cut. Our unique cross-conveyor scrap dump places scrap sod out of the way for the next pass or it can be accumulated and discarded at the end of the field. Neat stable stacks of turf are consistently produced and completed with an on-the-fly pallet exchange. The pallet injector holds 20 empty pallets, and a pallet lifter option for double-sided pallets is also available.



Cab rotates 90° into harvesting position for excellent visibility and operator comfort



FEATURES

- Powered by a 140 HP John Deere engine
- All-wheel hydrostatic drive with electronic traction control
- High floatation tires
- · Heated and air conditioned cab with air ride seat
- Cab rotates 90 degrees for enhanced operator visibility and comfort during harvest

(continued)

Trebro - TSR

Fully Self-Contained AUTOMATIC HARVESTER



Powered roll-up, automatic flap control system



Cross-conveyor scrap dump - puts scrap out of the way



FEATURES continued

- "CANBUS" Plus 1 Operating system with diagnostic interface
- Floating cutting head with adjustable dual down pressure
- Blade changing is easy and convenient with cutting heads in a locked raised position
- Outstanding maneuverability, tight turning radius
- Proven reliable Ultra Auto Steering system.
- · Automatic flap control for neat, stable stacks of turf
- Cross-conveyor scrap dump puts scrap out of the way
- Simplified stacker rotary actuator improves performance and reduces maintenance
- Can be easily set to stack flat top pallets or add in a tie in layer
- On-the-go automatic pallet injector with 20 pallet capacity
- Available in 16 inch, 21 inch, 23 inch or 24 inch cutting widths

SPECIFICATIONS

Width of Cut:	16 inches (.40 m) or
	21 inches (.53 m) or
	23 inches (.58 m) or
	24 inches (.61 m)
Length of Cut:	Electronically variable up to 81 inches
	(2.05 m)
Thickness of cut:	On-the-go hydraulic adjustment
Cutting Knife	One piece with fingers
Steering	Ultra-Steer Automatic, front pedestal
	170 degree arc
Weight:	26,600 lbs. (12,065 kg)
Length:	30 feet 2 inches (9.19 m)
Width:	11 feet 8 inches (3.55 m)
Height:	10 feet 5 inches (3.17 m)
Tires:	700-40-22.5 High Floatation Terra
Horsepower	.140 HP John Deere
Transmission:	Infinitely variable hydrostatic drive
All-Wheel-Drive	.All wheel electronic traction control

OPTIONS

Pallet Lifter for double sided pallets Remote service tool Spare Parts Package





